

NEW USERS READ FIRST:	Installation and usage instructions are on the 'Setup Instructions' tab below including links to purchase an OBDII adapter on Amazon. When FORScan is completely installed and setup, review the tutorial document linked in the FORScan Training section BEFORE making any changes. Don't forget to backup your modules first!							
Feature Name	As Built Module	Key Position	Example Value	New Value	Notes	FTE Member	Status	
TPMS (Tire Pressure Monitoring System) thresholds	BCM	726-40-01	xxxx 3C50 xxxx	xxxx 3C41 xxxx	3C41 indicates 60 psi front 65 psi rear. First two digits are front, second two are rear. Replace either of those two values with the desired PSI hex equivalent. (28=40 PSI, 2d=45 PSI, 32=50 PSI, 37=55 PSI, 3C=60 PSI, 41=65 PSI, 46=70 PSI, 50=80 PSI)	switch.	Multiple Confirmations	
Double Horn Honk Disable	BCM	726-41-02	xxx1 xxxx xxxx	xxx0 xxxx xxxx	This disables the double honk when walking away from truck with engine running and key fob in pocket. Recommended to implement the Secure Idle (Police Mode) feature to prevent unauthorized driving away without the key fob.	switch.	Multiple Confirmations	
Fog Lights with High Beam LED and some HALOGEN	BCM	726-27-01	xxxx xxx1 xxxx	xxxx xxx0 xxxx	This allows LED fog lights to stay on when high beams are also turned on. This code has been confirmed to work with some halogen headlight trucks also. Also known as Bambi mode (to see deer better).	switch.	Multiple Confirmations	
Fog Lights with High Beam HALOGEN	BCM	726-27-01	x0xx xxxx xxxx	x1xx xxxx xxxx	This allows Halogen fog lights to stay on when high beams are also turned on. Also known as Bambi mode (to see deer better).	KubotaOrange76	Multiple Confirmations	
Show Temps on Gauges	IPC	720-07-01	xxxx xEA xxxx	xxxx x**x xxxx	Display exact temperatures above the gauge on the center cluster. Replace ** with E5 with brake controller, 65 if no brake controller. A5 adds temps above gauges without adding boost gauge and boost data to menus.		Multiple Confirmations	
Heated and Cooled Seats Icons on Home and Climate Screens	APIM	7D0-01-01	xxxx xxxx x4xx	xxxx xxxx x**x	1 = Cooled seats option on screen, no heated seats or heated wheel option. 2 = Heated/cooled seats option on screen with no heated wheel option. 3 = Heated seats on screen, no cooled seats and no heated wheel option. 4 = No on screen heated/cooled seats on any screen, heated wheel is in top left. 5 = Unknown 6 = Heated/Cooled seats and heated wheel options on screen. 7 = Heated seats and heated wheel, no cooled seats. 8 = Rear Climate Control panel, no heated/cooled options for front.	AllGoNShow	Multiple Confirmations	
Fog Light Switches Off w/Blinker	BCM	726-28-02	xxxx x0xx xxxx	xxxx x1xx xxxx	Confirmed on LED and halogen headlights/fog lights. 0 (Default Operation - Fog Lights Constant), 1 (Fog Lights Switchback w/Blinker)	AllGoNShow	Multiple Confirmations	
Disable Door Lock Horn Honk	BCM	726-38-02	xxx1 xxxx xxxx	xxx0 xxxx xxxx	1 (Enabled - Default), 0 (Disabled)	AllGoNShow	Multiple Confirmations	
Secure Idle (Police Mode)	BCM	726-42-01	x0xx xxxx xxxx	x1xx xxxx xxxx	Prevents vehicle transmission from shifting out of Park without passive key inside vehicle (Shifter Locked w/No Key Detected message) 0=Disabled 1=Enabled	AllGoNShow	Multiple Confirmations	
Remember Fog Lights on Startup	BCM	726-27-01	xxxx x1xx xxxx	xxxx xxx0 xxxx	Default value does not remember either high beam or fog light status on key off/on. Headlight switch in Auto position. Restores previous setting only if lights are needed on next startup.	AllGoNShow	Multiple Confirmations	
Remember Fog Lights and High Beams on Startup	BCM	726-27-01	xxxx x1xx xxxx	xxxx xxx0 x1xx	Default value does not remember either high beam or fog light status on key off/on. Headlight switch in Auto position. Restores previous setting only if lights are needed on next startup.	AllGoNShow	Multiple Confirmations	
Speedometer Recalibration for Different Tire Size	BCM	726-12-01	xxxx xx00 xxxx	xxxx xx4C xxxx	Forum comment: "Original tire size 275/70r18, New size 285/75r18. No DTC codes after 900 miles. This is a small change. Larger tire size changes do calibrate the speedometer but a check engine light will persist." The following can be used for a slightly larger calibration (approx 2.5%) without CEL: xxxx-0AAE-xxxx	KubotaOrange76	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx x7xx xxxx	GT350 Boot Screen Animation *Sync 3.0 only	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx x9xx xxxx	GT350 Boot Screen Animation *Sync 3.0 only	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx x5xx xxxx	Raptor SVT Boot Screen Animation *Sync 3.0 only	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx x6xx xxxx	Mustang Boot Screen Animation *Sync 3.0 only	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx x4xx xxxx	Lincoln Presidential Boot Screen Animation *Sync 3.0 only	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	BCM	726-31-02		xxxx 07xx xxxx	Fixes Incorrect Color Choices When Using Lincoln Theme	Livinitup	Single Confirmation	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx x8xx xxxx	Vignale Boot Screen Animation *Sync 3.0 only	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx x5xx xxxx	Raptor Ford Performance Boot Screen Animation *Sync 3.0, Sync 2.2	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx xCxx xxxx	RS Boot Screen Animation *Sync 3.0, Sync 2.2	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx xBxx xxxx	RS Boot Screen Animation *Sync 3.0, Sync 2.2	RebelZ	Multiple Confirmations	
Sync 3 Boot Screen Animations	APIM	7D0-02-01	xxxx x1xx xxxx	xxxx xDxx xxxx	RS Boot Screen Animation *Sync 3.0, Sync 2.2	RebelZ	Multiple Confirmations	
Global Window Open/Close	BCM	726-17-01	0000 0000 0045	0101 0101 014A	Allows front windows to open/close with remote button. To open windows, press the unlock button once on fob, then press and hold the unlock button again until front windows begin opening. To close windows, press and hold the lock button for approximately 5 seconds and release when windows begin to close. Window movement can be interrupted at any time by pressing either the lock or unlock buttons.	RebelZ	Multiple Confirmations	
	BCM	726-17-02	0101 0101 014B	0101 0101 014B				
	BCM	726-30-01	0001 0000 005F	0101 xxxx xxxx				
	DDM	740-05-01	9A00 E7	Dxxx xxxx xxxx				
		PDM	741-05-01	8A00 D8	Dxxx xxxx xxxx			
	IPC	720-02-01	3xxx xxxx xxxx	7xxx xxxx xxxx	Adds new menu item under Advanced Settings/Vehicle/Windows to enable Remote Close. Remote Open or Close can be enabled and disabled using the checkboxes.	KYLongRifle	Multiple Confirmations	
Disable Panic Alarm Horn	BCM	726-01-02	xxx0 xxxx xxxx	xxx1 xxxx xxxx	Disables the horn when pressing the panic button on key fob. Lights will still flash.	Livnitup	Single Confirmation	
Panic Alarm Button Press Count	BCM	726-37-01	xxxx xxx2 xxxx	xxxx xxx* xxxx	Replace the asterisk with one of the following: 0=Panic alarm button on fob disabled, 1=Panic alarm button on fob requires 2 presses, 2=Panic alarm button on fob requires single press to activate.	Livnitup	Multiple Confirmations	

NEW USERS READ FIRST:	Installation and usage instructions are on the 'Setup Instructions' tab below including links to purchase an OBDII adapter on Amazon. When FORScan is completely installed and setup, review the tutorial document linked in the FORScan Training section BEFORE making any changes. Don't forget to backup your modules first!						
Enable/Disable Spot Lights	BCM	726-56-01	xxxx x1xx xxxx	xxxx x0xx xxxx	1 for enable, 0 for disable	Livnitup	Single Confirmation
Disable Tire Pressure Monitor	BCM	726-08-01	x1xx xxxx xxxx	x0xx xxxx xxxx	1 for enable, 0 for disable	Livnitup	Multiple Confirmations
Timeouts for Heated Steering Wheel	HSWM	714-01-01	*xxx xxxx xxxx	*xxx xxxx xxxx	HSWM is Heated Steering Wheel Module. Replace the asterisk with one of the following: 1=Timeout disabled, 8=5 mins, 9=10 mins, A=12 mins, B=15 mins, C=18 mins, D=20 mins, E=25 mins, F=30 mins	Livnitup	Not confirmed, possible F150 only module
Parking lamps on with low beams for DRL	BCM	726-26-02	x0xx xxxx xxxx	x1xx xxxx xxxx	Enables parking lamps while headlights are on low beam when in DRL (daytime running lights).	Livnitup	Waiting Confirmation
Remove CD Option from Sync	APIM	7D0-04-01	x1xx xxxx xxxx	x0xx xxxx xxxx	Remove the CD player from source in the Sync screen	Livnitup	Multiple Confirmations
Remove Sirius from Sync	APIM	7D0-01-01	*xxx xxxx xxxx	8xxx xxxx xxxx	Removes Sirius as a media source in Sync. If * is A change to 8, if 2 change to 0. Change does not take effect immediately. Turn truck off, open and shut door, wait 30 seconds and restart.	Texmudder	Multiple Confirmations
Courtesy Lamps Ramp Down	BCM	726-32-02		xx** xxxx xxxx	Courtesy Lamps ramp down duration (seconds converted to hex)	Livnitup	Waiting Confirmation
Courtesy Lamps Ramp Up	BCM	726-32-02		xxxx x** xxxx	Courtesy Lamps ramp up duration (seconds converted to hex)	Livnitup	Waiting Confirmation
Courtesy Lamps Configuration	BCM	726-31-01		xxxx x*xx xxxx	Courtesy Lamps Cfg: 0=immediate, 1=Theater Dimming	Livnitup	Waiting Confirmation
Puddle Lights Show Time	BCM	726-31-01		xxxx xxxx **xx	Approach (Puddle) Light Show Max Time (seconds converted to hex). When truck unlocked via fob.	Livnitup	Waiting Confirmation
Change Fuel Tank Size	IPC	720-03-01	xxx* **xx xxxx	xxx* **xx xxxx	Change asterisks to one of the following: 30 Gal=4 4A, 34 Gal=5 07, 40 Gal=5 EA, 48 Gal=7 19, 50 Gal=7 65, 55 Gal=8 22, 60 Gal=8 DF, 68 Gal=A 0E, 70 Gal=A 5A (This parameter is in Liters in this format XXX.x. 55gal equals 208.198L so round to 208.2 and drop the decimal to get 2082. Convert decimal value 2082 to HEX equals 822 or 8 22.)	KYLongRifle	Multiple Confirmations
Driver Seat Belt Chime Disable	IPC	720-01-01	xxxx xx6x xxxx	xxxx xx2x xxxx	Number 2 in this position disables the chime on the driver seat	jjmcc2	Waiting Confirmation
Passenger Seat Belt Chime Diable	IPC	720-01-01		xxxx xx4x xxxx	Number 4 in this position disables the chime on the passenger seat	jjmcc2	Waiting Confirmation
Disble all Seat Belt Chimes	IPC	720-01-01		xxxx xx0x xxxx	Number 0 in this position disables the chime on the driver and passenger seats. NOTE: Seat belts can be disabled via instructions in the owners manual	jjmcc2	Multiple Confirmations
Autofold/Unfold Mirrors via Lock/Unlock on Fob	DDM	740-03-01		x8xx xx	Autofold mirrors via unlock/lock on fob. ** Tow mirrors require swapping pins 18 & 19 on mirror connector. See link: http://www.f150forum.com/f118/tow-mirrors-auto-fold-mod-pictures-365884/ . Fxxx works on trucks with 2 key fobs but FCxx is required if using 3 or 4 key fobs.	hollapm	Multiple Confirmations
	DDM	740-12-01		Fxxx or FCxx			
	PDM	741-03-01		x8xx xx			
	PDM	741-12-01		Fxxx or FCxx			
Autofold/Unfold Mirrors (Lincoln Style)	DDM	740-03-01		x84x xx	Autofold mirrors - Lincoln Style (doesn't unfold/fold with unlock/lock on fob...requires opening/closing door). ** Tow mirrors require swapping pins 18 & 19 on mirror connector. See link: http://www.f150forum.com/f118/tow-mirrors-auto-fold-mod-pictures-365884/ . Fxxx works on trucks with 2 key fobs but FCxx is required if using 3 or 4 key fobs.	hollapm	Multiple Confirmations
	DDM	740-12-01		Fxxx or FCxx			
	PDM	741-03-01		x84x xx			
	PDM	741-12-01		Fxxx or FCxx			
Sync 3 Theme - Ford GT (Blue)	APIM	7D0-01-02		0xxx xxxx xxxx	Changes the Sync 3 screens to a GT theme. Splash screen will change to GT.	Livinitup	Multiple Confirmations
		7D0-02-01		xxxx xDxx xxxx			
		7D0-03-01		xxxx x4xx xxxx			
Increase radio on time after truck shut down	APIM	7D0-01-01	xx2x xxxx xxxx	xx6x xxxx xxxx	This changes the radio power-off delay to 60 minutes after the truck is shut off. Wait for the ignition power to time out and then turn the radio back on with the RADIO power button. Alternatively, after turning off the ignition, open and close any door to disable accessory power. Then press the radio power button to turn radio back on. It will now stay on for the extended time amount.	Livinitup	Multiple Confirmations
Add DPF Filter % to screen	IPC	720-07-02	x7xx xxxx	xFxx xxxx	This adds the DPF % screen to the Truck Information screen. Some trucks will report a camera error after making this modification. To avoid this, update according to the following: If original default value is 0, change to 8; if 1, change to 9; if 2 then A; if 3 then B; if 4 then C; if 5 then D; if 6 then E, if 7 then F.	screwy	Multiple Confirmations
Enable Auto-Regen Checkbox	IPC/PCM	720-07-02	Plain English	Not HEX	Enable auto regen in IPC and select option 3 under "DPF manual regeneration" in PCM (not as built).	screwy	Multiple Confirmations
Power Point Timeout Disable	BCM	726-39-01	xxxx x1xx xxxx	xxxx x0xx xxxx	Turns off the timeout on the power points in the truck. Battery Monitoring System (BMS) will override unless disabled. This feature has had multiple confirmations but also failed on other trucks. Differences are unknown.	Livinitup	Multiple Confirmations
Power Point Timeout 4 Hours	BCM	726-39-01	xxxx x1xx xxxx	**** xxxx xxxx	Replace the **** with 3870. Allows power points to remain powered for 4 hours after the vehicle is shut down. After four hours the power points will timeout and stop supplying voltage to plugged in devices. This feature has had multiple confirmations but also failed on other trucks. Differences are unknown.	manowell	Single Confirmation
Battery Monitoring System (BMS) Disable	BCM	726-04-01	xxx1 xxxx xxxx	xxx0 xxxx xxxx	Disables battery protection system. Electrical systems will remain on and vehicle batteries can drain completely. THIS MAY NOT WORK. The default value is already 0, not 1 as shown. Waiting additional updates.	Livinitup	Waiting Confirmation
		726-45-01		xxxx 7Fxx xxxx	Allow DRL choices below:		

NEW USERS READ FIRST:		Installation and usage instructions are on the 'Setup Instructions' tab below including links to purchase an OBDII adapter on Amazon. When FORScan is completely installed and setup, review the tutorial document linked in the FORScan Training section BEFORE making any changes. Don't forget to backup your modules first!						
Daytime Running Lights (DRL)	BCM	726-50-01		xxxx **xx xxxx	Replace ** with the two digit value of the desired lights to illuminate in DRL mode. 01 = DRL Master Disable 02 = Low Beams 04 = Front Fog Lamps 08 = Front Turn Lamps 10 = Dedicated DRL Lights (LED Light Bars/Strips) - Enables BCM DRL Outputs 20 = High Beams 40 = Low Beams and Dedicated DRL Lights Hex addition of all the choices above: 10+01+02+04+08+20+40=7F Example 1: A truck with LEDs would have an as-built value of 726-45-01 xxxx 11xx xxxx which would only allow values at 726-50-01 of Dedicated DRL Lights (10) or DRL disabled (01) = (Hex addition of 10 + 01 = 11) Example 2: A truck with Halogens would have an as-built value of 726-45-01 xxxx 03xx xxxx which would only allow values at 726-50-01 of DRL disabled (01) or DRL low beams (02) = (Hex addition of 01 + 02 = 03)	DanMc85 & Livinitup	Single Confirmation	
Outer Halo Lights as DRLs	BCM	726-26-02 726-50-01		x1xx xxxx xxxx 017F	Outer halo lights as DRLs (no low beam, no turn signals). Confirmed on F150s but waiting confirmation on SDs	Livinitup	Waiting Confirmation	
Halogen to LED Headlight Conversion	BCM	726-26-02	xxxx xxx1 xxxx	xxxx xxx0 xxxx	Frequency select configuration: 0 = default for OEM LED; 1 = default for OEM Halogen. Excellent tutorial that goes beyond the instructions provided here: https://www.ford-trucks.com/forums/1517743-complete-how-to-halogen-to-led-heads-and-tails.html (thanks to jmeo for the contribution)	Livinitup & jmeo	Waiting Confirmation	
Halogen to LED Rear Turn Signal Conversion	BCM	726-27-02		xxxx xxxx x*xx	Rear bulb turn outage config: 1=outage, 0=no outage			
Bluetooth Pairing Name	APIM	7D0-04-01		xxxx xxxx **xx	This changes the device name of the truck when pairing bluetooth devices. Change the asteriscs with: 2D=Raptor, 0E=F150, 0F=F250, 10=F350, 19=MKZ, 02=Focus, 03=Fusion, 04=C-Max, 06=Mustang, 08=Escape, 09=Edge, 24=Mondeo, 0B=Explorer, 20=Fiesta, 1B=MKC, 2E=Continental, 1C=MKX, 1E=Navigator, 0C=Expedition. ** The above only works in Sync 3 ver 2.0+ and if you wish to change it you must remove paired phone from Sync 3 & paired name from phone and re-pair.	Livinitup	Waiting Confirmation	
Average Speed Display	IPC	720-01-01	xxxx x1xx xxxx	xxxx x4xx xxxx	Adds "Average Speed" menu item to the Trip/Fuel menu.	Livinitup	Multiple Confirmations	
Massage Seats	SCMG/SCMH	Multiple		See link	Link to F150 Spreadsheet for all values	Livinitup	Waiting Confirmation	
Turn Signal Flash Count	SCCM	724-01-01	xxxx x6xx xx	xxxx x*xx xx	Replace * with one of the following: 0=1 Flash OUC False 1=1 Flash OUC True 2=1 Flash OUC False 3=1 Flash OUC True 4=2 Flashes OUC False 5=2 Flashes OUC True 6=3 Flashes OUC False 7=3 Flashes OUC True 8=4 Flashes OUC False 9=4 Flashes OUC True A=5 Flashes OUC False B=5 Flashes OUC True C=6 Flashes OUC False D=6 Flashes OUC True E=7 Flashes OUC False F=7 Flashes OUC True On Until Cancelled (OUC) means manually moving the turn signal arm in opposite direction or manually cancelling the turn signal. Two flashes are added automatically when trailer is attached.	Livinitup	Multiple Confirmations	
Switch Steering Wheel Buttons	SCCM	724-01-01	xxxx 0xxx xx	xxxx 8xxx xx	If you like your stereo buttons on the left instead of the right this value will swap button functions from right bank to left bank. Note: This is only for the Up,Down,Right,Left/Center buttons. Not the lower set for cruise control, voice commands, etc. Cluster Crossover Cfg: 0=disable, 8=enable	Livinitup	Waiting Confirmation	
Ambient LED Lighting (Door Ajar)	BCM	726-31-01		x*xx xxxx xx	Replace * with one of the following: 0=Ice Blue (Ford), 1=Orange (Ford), 2=Soft Blue (Ford), 3=Red (Ford), 4=Green (Ford), 5=Blue (Ford), 5=Purple (Ford), 7=White (Lincoln), 8=Amber (Lincoln), 9=Teal (Lincoln), A=Red (Lincoln), B=Blue (Lincoln), C=Green (Lincoln), D=Lilac (Lincoln), E=Unknown, F=Unknown. Note: Sync 3: Use Lincoln Splash Screen Brand (7D0-01-02 8xxx xxxx xx--), on your APIM so that on screen color selections will match BCM if you use a color greater than or equal to 7 .	flsdiver	Single Confirmation	
Ambient LED Lighting (Entry)	BCM	726-31-02		xxxx x*xx xx	Replace * with one of the following: 0=Ice Blue (Ford), 1=Orange (Ford), 2=Soft Blue (Ford), 3=Red (Ford), 4=Green (Ford), 5=Blue (Ford), 6=Purple (Ford), 7=White (Lincoln), 8=Amber (Lincoln), 9=Teal (Lincoln), A=Red (Lincoln), B=Blue (Lincoln), C=Green (Lincoln), D=Lilac (Lincoln), E=Unknown, F=Unknown. Note: Sync 3: Use Lincoln Splash Screen Brand (7D0-01-02 8xxx xxxx xx--), on your APIM so that on screen color selections will match BCM if you use a color greater than or equal to 7 .	flsdiver	Single Confirmation	
Add Hill Descent Control	ABS	760-03-01	x1xx xx	x3xx xx	This feature requires addition of an activation button on the dash. Replace the hazard button with a dual function hazard and HDC enable button part #: HC3Z-13D730-CA. For more information see the following thread: https://www.ford-trucks.com/forums/1503198-forscan-adding-hill-descent-control-to-non-fx4-4x4.html	Mooch91	Single Confirmation	

NEW USERS READ FIRST:	Installation and usage instructions are on the 'Setup Instructions' tab below including links to purchase an OBDII adapter on Amazon. When FORScan is completely installed and setup, review the tutorial document linked in the FORScan Training section BEFORE making any changes. Don't forget to backup your modules first!						
Add TPMS "Specified" to display	IPC	720-04-01		xx*x xxxx xxxx	Replace * with one of the following: 0=TBC Gain disabled & TPMS Specified value disabled 4=TBC Gain enabled & TPMS Specified value disabled 8=TBC Gain disabled & TPMS Specified value enabled C=TBC Gain enabled & TPMS Specified value enabled	Livinitup	Multiple Confirmations
Disable Traction Control	IPC	720-01-01		xx2x xxxx xxxx	AdvanceTrac Disabled	Livinitup	Single Confirmation
Enter NAV Destination and viewing texts while vehicle is in motion	APIM	7D0-02-01		5753 xxxx xxxx	Enables entering NAV destination and viewing texts while vehicle is in motion. Sync version must be upgraded to version 2.2 or higher. Instrction for upgrading Sync begin on post 2044 Page 52 of the FORScan spreadsheet. https://www.ford-trucks.com/forums/1460787-forscan-spreadsheet-52.html . Ahem, do we need to say it? This feature should be used by the passenger and the driver should keep their eyes on the road. Be smart and be safe. This feature disables automatic 911 calling if in an accident.	Livinitup	Multiple Confirmations
Disable Door Chime when Door Ajar	IPC	720-01-02	xx1x xxxx xxxx	xx0x xxxx xxxx	Disables door chime when door open and ignition on.	neonovulator	Multiple Confirmations
Disable Key In Ignition Chime	IPC	720-02-01		xx*x xxxx xxxx	This disables chime when key is in the igation and ignition is off. Subtract 8 from the value in the * position. For example, if C then change to 4. This feature is dependent upon the Disable Door Chime when Door Ajar feature. That must be enabled first for this to work.	neonovulator	Multiple Confirmations
Disable Illuminated Entry/Exit - Dark Car Mode	BCM	726-32-01		xxxx x1xx xxxx	Turns off parking and cargo lights when door is opened.	R1xterGonz0	Single Confirmation
	BCM	726-58-02		xxxx xxxx x1xx	Silent mode. Waiting for better description		Single Confirmation
Remote Start Enable/Disable	BCM	726-22-02		xxx* xxxx xxxx	Substitute * with one of the following: 0=disabled, 1=enabled	Livinitup	Waiting Confirmation
Add Climate Screen for XL/XLT	APIM	7D0-01-01		xxxx xxx3 xxxx	Adds climate screen to Sync v3 and above XL and XLT trims. Note: Fan speed control does not work, remains on the analog dial, Does not add dual climate capabilities, Temp control does not work, remains on the analog dial. What does work- On/Off, AC & Recirculate On/Off, Vent Control - foot, dash, windshield, Some voice commands	Uzumati	Single Confirmation
	APIM	7D0-01-02		xxxx x2xx xxxx			
Ambient Light Sensor Speed	BCM	726-26-01		xxx* xxxx xxxx	0=15 seconds delay turning on headlamps when dark, 1=2 seconds delay turning on headlamps when dark	Livinitup	Single Confirmation
Speedometer Calibration for 37 inch Tires	BCM	726-12-01		0163 0ACC xxxx	This update will correct the speedometer to read accurately for the larger tire size. It will however, also set a check engine light (CEL) because of the difference from factory settings. There appears to be no other negative effects other than the CEL.	KubotaOrange76	Multiple Confirmations
Disable Triple Ding at Startup	IPC	720-01-02		xxxx x2xx	Turns off "ding ding ding" at start up.		
DRL to Full Bright w/Headlights	BCM	726-29-02		x1xx xxxx xxxx	Stops DRL's from dimming when headlights are in the On, Parking, and Auto positions.	Tippmann7641	Multiple Confirmations
DRL Turn Signal Switchback	BCM	726-26-02		xxxX xxxx xxxx	Turn signal turns the DRL off. 0 = Diasabled 1 = Enabled	Anibal Medina	Multiple Confirmations
Auto-Engine Shutdown Disable	BCM	726-22-01		xxxx xxx0 xxxx	Ignition Power Shutdown Enable Cfg: 0=disable, 1=enabled	Livinitup	Multiple Confirmations
Radio Extended Play	APIM	7D0-01-01		xx*x xxxx xxxx	RadioExtended Play: A=off, 2=20mins, 3=30mins, 4=40mins, 5=50mins, 6=60mins (Sync 2 & Sync 3)	Livinitup	Multiple Confirmations
IPC Quick Boot (No Ford animation shows on cluster)	IPC	720-07-01		xxxx xxxx *xxx	2=Enable quick boot	Livinitup	Multiple Confirmations